



DESIGNING FOR TOMORROW'S DEMANDS

14V OUTPUT	MODEL	OUTPUT AT IDLE estimated at 2000 alternator rpm and 200 degrees F.	DESCRIPTION	MOUNTING BRACKET	TENSION BRACKET	ALIGNMENT rear of front foot to pulley bushing	SHELL DIAMETER	LENGTH pulley bushing to anti-drive end	REGULATOR	PHOTO
280A	C510	145A	Externally Rectified	J180 4" hinge	one .5" bolt	J180 - 1.18"	7.25"	8.22"	A2-136	F
290A	C623	180A	Tapered housing	Custom 7" hinge	two .375" bolts, spaced 3.36"	J180 - 1.18"	7.75"	10.79"	A2-128	D
	C628		one M12 bolt		J180 - 1.18"	8"	11.53"	A2-155	E	
	A1-608*		Square shaped housing	J180 4" hinge	one .5" bolt	J180 - 1.18"	7.75"	10.79"	A2-121	A
300A	C502	150A	Round housing	J180 4" hinge	one .5" bolt	J180 - 1.18"	7.5"	8.29"	A2-334	C
	C524		Pad Mount	Fixed Pad Mount	N/A	N/A	7.5"	8.49"	A2-334	B
340A	C619	210A	Square shaped housing	J180 4" hinge	one .5" bolt	J180 - 1.18"	7.75"	10.79"	A2-121	A
	C620		Tapered housing	Custom 7" hinge	two .375" bolts, spaced 3.36"	J180 - 1.18"	7.75"	10.79"	A2-128	D
	C627		Square shaped housing		one M12 bolt	J180 - 1.18"	8"	11.53"	A2-155	E
360A	C616	170A	Externally Rectified	J180 4" hinge	two 13mm bolts, spaced 6"	J180 - 1.18"	7.75"	8.48"	A2-136	F
	C715	150A	Tapered housing	Custom 7" hinge	two .375" bolts, spaced 3.36"	Custom - 1.62"	8"	12.06"	A2-128	G
400A	C656	225A	Square shaped housing	Custom 7" hinge	one M12 bolt	J180 - 1.18"	8"	11.53"	A2-155	E*
	C657			J180 4" hinge						
	C671		Tapered housing	Cradle Mount	two .75" bolts, spaced 3.36"	Custom - 2.83"	7.75"	10.98"	A2-155	N/A
	C714*	Square shaped housing	Custom 7" hinge	two .375" bolts, spaced 7"	Custom - 1.62"	8"	12.06"	A2-155	N/A	
	C716	210A		Tapered housing	two .375" bolts, spaced 3.36"	Custom - 1.62"	8"	12.06"	A2-128	G
600A	C525 (2)	300A	Dual Pad Mount w/ Single Regulator	Fixed Pad Mount	N/A	N/A	7.5"	8.49"	A2-324	B



A



B



C



D



E



F



G

*** Service Notes:**

- A1-608 is the service replacement for OEM Models N1222 & N1223
 - C714 upgrades both C711 & C712

- Photo E represents C657 which is identical to C627, C628, and C656 (as pictured) with the exception of a shorter, four inch distance between mounting feet (not shown).

The above information is for reference only.
 For detailed dimensions and/or additional information,
 please call 847-866-6030 or e-mail sales@CENiehoff.com
 LIT-FIREORC08